



# BARRIER WASHER EXTRACTORS

## POWER, CONTROL AND TOTAL DESINFECTION

### FEATURES

- High spin soft mounted washer extractor, no need of anchorage, 2 opposed doors.
- Capacity 33 kg.
- Extraction speed 990 Rpm.
- G force 400.
- Body, drum and vat in stainless steel.
- Horizontally suspended drum by means of two axles which increase robustness, 1 compartment.
- Soap dispenser with 4 compartments.
- 8 signals for liquid dosing.
- Three water inlets standard in all range.
- Out of balance detection by means of the inverter.
- New TOUCH microprocessor with a lot of devices for a greater flexibility. 26 preset programs, unlimited creation of new programs.
- WET CLEANING system integrated (standard).
- OPTIMAL LOAD system integrated: manual indication of load.
- Traceability - storage of data.
- Electric or steam heating.
- Standard double display.

### ASM-35 TOUCH



### OPTIONS

- 2nd drain valve.
- Central position drain valve.
- Detergent bath sampling.
- Weighing sensor system on feet.
- Electric brake.
- Relay card to increase up to 14 signals for liquid dosing.
- Dual heating electric+steam.
- Plinth up to height 850mm door bottom.
- Stainless steel wall frame.

Touch  
Technology

Stainless  
Steel  
Standard

Hot & Cold  
MIX

Imbalance  
Inverter

WET  
Cleaning

Optimal  
Loading

Easy  
Maint.

Soft  
O-Recycle

Auto  
Weight