



## COMPACT FLATWORK IRONERS

SHEER PRODUCTION VOLUME IN REALLY REDUCED SPACES

### FEATURES

- Flatwork ironers with roll sizes: 2.600 and 3.300 mm wide and 1.000 mm diameter.
- Panels in painted steel.
- One or two working lanes: one lane for bedsheets and two lanes for tablecloths and small pieces.
- Length fold with 1 or 2 folds in two independent lanes.
- Folding by photocells and compressed air.
- Frequency control.
- Feeding and ironing belts are Nomex.
- Polished steel roll, with finger guard.
- CE certificate and gas certifications.
- Touch-screen control: programs can be created with speed control (between 3 and 18 mts/min), temperature and folding parameters.
- Big output capacity, depending on the residual moisture of the linen, up to 290 kg/hour straight from the high spin washer extractor.
- Electric, gas or steam heating.
- Powerful exhaust System.
  - **NEW** gas model with **standard radiant burner.**  
**25% gas consumption savings and 25% more production.**

### CEPHEUS CE26100-33100



### OPTIONS

- Automatic 1 lane clamp feeder with vacuum feeding belts.
- Small pieces back collector: 2 or 4 lanes.
- Vacuum feeding belts.
- Linen reject system.
- Double air pressure in length folds for thicker linen.
- Rear exit with by-pass included.
- Motorized rear exit - height of 850 mm.
- Cross folder PL-Cross + stacker for Cepheus.
- Special voltage.



SECADO DRYING

PLIEGUE LONGITUDINAL LENGTH FOLD



PLANCHADO IRONING

