


TECHNICAL DATA	UNIT.	DHS-27 TOUCH	DHS-36 TOUCH			
DRUM						
Load capacity 1:9 / 1:10	Kg	28/25	39/35			
Volume	l	250	350			
Diameter	mm	770	860			
Depth	mm	530	602			
GENERAL DETAILS						
Washing speed / Spining speed	r.p.m.	45/1.035	42,5/975			
G Factor	-	450	450			
Maximum force transmitted	KN	4,9 ±1,75	7,5 ±2,45			
Frequency-dynamic force	Hz	15	14,3			
Sound level	dB	70	70			
Self-service version	-	Yes	Yes			
Double drain	-	Opt	Opt			
Weighing System / Tilting System	-	Opt/No	Opt/No			
DOOR						
Height center door / Height door	mm	865/600	885/540			
Diameter	mm	373	560			
POWER						
Motor	kW	3	4			
Heating (Electric model)	kW	18	21			
Max. power (Electric model)	kW	19	22			
Max. power (steam and hot water)	kW	3	4			
CONEXIONES		ELECTRICAL	STEAM / HOT WATER	ELECTRICAL	STEAM / HOT WATER	
Tension 230V- I + N +T	Nº x mm2 / A	3 x 25 / 100A	3 x 1,5 / 16A	-	-	
Tension 230V - III + T	Nº x mm2 / A	4 x 10 / 50A	-	4 x 25 / 100A	4 x 1,5 / 6A	
Tension 400V - III + N + T	Nº x mm2 / A	5 x 4 / 32A	-	5 x 16 / 63A	5 x 1,5 / 16A	
Steam inlet (Steam mod.)	inch	3/4"		3/4"		
Maximum steam consumption (Steam mod.)	Kg/h	15		18		
Water inlet	inch	3/4"		3/4"		
Water main pressure	Kgs/cm ²	2-4		2-4		
Maximum water consumption*	Lit/h	175,5		261,3		
Drain	mm/inch	3"		3"		
Drainage capacity	Lit/min	200		200		
DIMENSIONS / PACKING DIMENSIONS						
Width / Width	mm	979/1.060			1.095/1.190	
Depth / Depth	mm	1.041/1.180			1.184/1.250	
Height / Height	mm	1.553/1.810			1.598/1.870	
Net weight / Gross weight	kg	502/548			762/818	

* N°20 Program, 75% load



01. Soap dispenser
02. Emergency stop
03. Usb port
04. Drain
05. Electric connection to liquid soap pumps
06. Electrical connection
07. Main switch
08. Auxiliar water inlet
09. Hot water inlet
10. Ground connection
11. Cold water inlet
12. Blur output / water overload
13. Liquid soap connection
14. Steam connection

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U
DHS-27	979	1.041	1.553	610	373	130	532	1.279	1.343	1.282	1.462	1.462	61	74	101	506	586	864	906	367	909
DHS-36	1.095	1.184	1.598	522	560	155	990	1.326	1.494	1.344	1.509	1.509	61	74	101	621	701	979	1.021	384	1.024